

BEAM CLAMP

A Beam clamp can be used to suspend manual, electric or an air hoist from a suitably rated beam or gantry. For safety reasons, we fully recommend you to ensure the beam that you are suspending from should fit the purpose

- Compact, Quick & easy installation.
- Designed to provide a quick and versatile rigging point for all types of hoisting equipment.
- Eliminates the requirement for drilling, welding or other attachment techniques.
- Efficient and safe application



Model	Capacity (kg)	Adjustable Beam Width (mm)	Dimension										Net Weight (kg)
			A <small>Max (mm)</small>	B <small>Min (mm)</small>	B <small>Max (mm)</small>	C <small>mm</small>	D <small>mm</small>	E <small>mm</small>	F <small>Min (mm)</small>	F <small>Max (mm)</small>	G <small>mm</small>	H <small>mm</small>	
LEBC-1	1000	73-230	278	180	370	62	5	230	100	160	30	25	4
LEBC-2	2000	75-230	278	180	370	67	6	230	100	160	35	28	4.4
LEBC-3	3000	80-320	356	230	480	100	8	260	125	210	45	32	8.6
LEBC-5	5000	80-320	356	230	480	110	10	260	125	210	50	38	10.7
LEBC-10	10000	80-320	356	255	490	115	12	270	170	240	65	43	14.5

